

M Performance

Kanalv 9
792 33 Mora
Sweden
(46) 2 501 1321

DYNomite Test Run: Fusion 600 -06

Date: 13/12/2005

Correction Method: Standard

RPM	(RFSec	(Second	Hp (H)	Torque (ft	FuelMass (lb	Bensin (liter	BSFC (lb/Hp	Air Temp (Degree	Baro (in H	Humid (%)
4000	0.457	24.66	32.44	41.00	25.85	1.66	11.1	29.91	59	
4100	1.081	21.94	28.24	40.38	25.46	1.84	11.1	29.91	59	
4200	1.300	21.76	27.29	41.32	26.05	1.90	11.1	29.91	59	
4300	1.425	23.80	29.09	42.37	26.72	1.78	11.1	29.91	59	
4500	1.570	27.69	32.49	44.40	28.00	1.60	11.1	29.91	59	
4700	1.700	30.88	34.72	47.05	29.67	1.52	11.1	29.91	59	
4900	1.825	32.87	35.45	49.51	31.22	1.51	11.1	29.91	59	
5100	1.980	34.70	35.80	51.77	32.65	1.49	11.1	29.91	59	
5200	2.058	35.71	36.11	52.49	33.10	1.47	11.1	29.91	59	
5400	2.238	38.44	37.38	53.05	33.45	1.38	11.1	29.91	60	
5500	2.326	39.67	37.97	52.97	33.40	1.33	11.1	29.91	60	
5600	2.456	41.36	38.83	52.42	33.06	1.27	11.1	29.91	60	
5700	2.630	43.65	40.21	51.95	32.76	1.19	11.1	29.91	60	
5800	3.042	48.17	43.79	53.53	33.76	1.11	11.1	29.91	60	
5900	4.743	63.75	56.80	59.52	37.53	0.93	11.1	29.91	60	
6000	5.277	65.94	57.68	60.85	38.37	0.92	11.1	29.91	60	
6100	5.751	66.80	57.56	62.55	39.44	0.94	11.1	29.91	60	
6200	6.153	68.23	57.73	63.20	39.85	0.93	11.1	29.91	60	
6300	6.606	69.42	57.92	64.24	40.51	0.93	11.1	29.91	60	
6400	7.189	70.95	58.03	67.15	42.34	0.95	11.1	29.91	60	
6500	7.887	72.62	58.63	65.87	41.54	0.91	11.1	29.91	60	
6600	8.399	74.23	59.19	71.83	45.30	0.97	11.1	29.91	60	
6700	9.305	76.47	60.06	74.37	46.89	0.97	11.1	29.91	60	
6800	8.916	80.55	62.19	77.49	48.86	0.96	11.1	29.91	60	
6900	10.19	81.88	62.55	74.25	46.82	0.91	11.1	29.91	60	
7000	10.31	86.89	65.20	74.42	46.93	0.86	11.1	29.91	60	
7100	10.87	88.45	65.39	75.13	47.38	0.85	11.1	29.91	60	
7200	12.32	88.71	64.74	76.95	48.52	0.87	11.1	29.91	60	
7300	13.07	92.25	66.51	78.62	49.57	0.85	11.1	29.91	60	
7400	13.19	96.58	68.69	78.91	49.76	0.82	11.1	29.91	60	
7500	14.07	101.8	71.38	81.49	51.39	0.80	11.1	29.91	60	
7600	15.49	102.2	70.63	84.81	53.48	0.83	11.1	29.91	60	
7700	16.03	107.1	73.12	84.19	53.09	0.79	11.1	29.91	61	
7800	16.97	108.1	72.91	85.57	53.96	0.79	10.8	29.91	61	
7900	18.76	110.7	73.20	87.81	55.37	0.79	10.6	29.91	62	
8000	19.32	108.2	71.13	87.95	55.46	0.81	10.6	29.91	62	
8100	19.96	110.2	71.31	88.30	55.68	0.80	10.6	29.91	63	
8200	20.91	110.8	71.13	91.08	57.43	0.82	10.6	29.91	63	
8300	22.00	108.9	69.22	90.64	57.16	0.83	10.6	29.91	64	